

## REWIRING OF THE AIRBLOC ACT LOW VOLTAGE RELAYS.



### INDEX

### Section

General information .....	1
Tools and parts requirement .....	2
Step by step instruction .....	3

### WARNINGS

All installations should be in accordance with the relevant requirements of Building Regulations, Local Authority Byelaws and I.E.E. Regulations and Units should be wired by a competent, qualified Electrician.

### Tools required.

The following tools and equipment will be required to complete this task:

1. Rewiring kit pt no 900365 (as a retrofit for the ORIGINAL configuration).
2. Rewiring kit pt no 900366 (as a retrofit for the MODIFIED configuration).
3. Electrical screwdriver.
4. Small pozi screwdriver.

### General Information.

Where re-wiring of the ACT low voltage relays are required, the following instructions will need to be carried out.

The information contained in this technical bulletin is designed to aid a qualified or competent service technician in the instruction it is in-

tended for.

There are two versions of the options currently out in the field. The following pages will be split into two halves. Note your particular Airbloc ceiling tile type and follow the instructions to suit.

The original configuration consisted of a wiring 'tray' attached to the front of the wiring contractors terminal enclosure. This houses a 24V relay and base, a 24V relay and a 5 way terminal block (see fig.2 below).



fig.2 original contractors box configuration

This type is identified by its four **YELLOW** wiring spade connectors, connected to the clear relay.



The second configuration houses a 24V relay and base, a 24V relay and a 5 way terminal block within the contractors terminal enclosure box itself (see fig.3 below).



fig.3 Modified wiring tray configuration

This type is identified by its two **YELLOW** wiring spade connectors & two **BLUE** wiring spade connectors, connected to the clear relay.



## Step by step instructions.

**Warning**  
Ensure electrical power is isolated from the product.

For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.

For ease of maintenance it may be advisable to firstly remove the ceiling tile. For information on how this is achieved, please refer to the Installation instruction manual.



1. Using a small pozi screwdriver, remove the **THREE** screws. Retain for later.


For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.

For ease of maintenance it may be advisable to firstly remove the ceiling tile. For information on how this is achieved, please refer to the Installation instruction manual.




1. Using a small pozi screwdriver, remove the **FOUR** screws. Retain for later.


For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.




2. Remove the terminal connectors from the **CLEAR RELAY** as shown in the photo.



3. Remove the **RED** cable from **BLACK RELAY n.o. terminal 14**




4. Remove the two **RED** cables from **terminal 2**




5. Remove the **BLACK** cable from **BLACK RELAY COIL terminal A2**


For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.




2. Remove the terminal connectors from the relay as shown in the photo above



3. Remove the **BROWN** cable from **BLACK RELAY com. terminal 11**




4. Remove the **RED** and **BROWN** cables from **terminal L1**




5. Remove the **BROWN** cable from **BLACK RELAY n.o. terminal 14**


For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.



6. Remove the two **BLACK** cable from **terminal 5**



7. Remove the **RED** cable from **terminal 4**




8. Remove the **RED** cable from **BLACK RELAY COIL terminal A1**




9. Remove the **RED** cable from **terminal 3**


For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.




6. Remove the **BROWN** cable from **terminal 5**



7. Remove the **RED** cable from **terminal H1**




8. Remove the **TWO GREY** cables from **BLACK RELAY terminal A2**



9. Remove the **GREY** cable from **terminal 02**


For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.




10. Remove the **RED** cable from terminal L




11. Pull the **RED** cable through the sleeving and dispose.



12. Remove the **CLEAR RELAY** by first removing the self tapping screw, then loosening the screw on the opposite side (see above). Replace using a new **CLEAR RELAY** and position using the same two screws (see below).



For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.



10. Remove the **RED** cable from **terminal 01**




11. Remove the **CLEAR RELAY** by first removing the self tapping screw (see above), then withdrawing the relay (see below). Replace using a new **CLEAR RELAY** and position using the same screw.




12. Locate the rewiring kit of cables. Using the short **GREY** cable, push the spade connector onto bottom right hand **CLEAR RELAY** terminal no. **A2**

For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.




13. Locate the rewiring kit of cables. Using the short **RED** cable, push the spade connector onto bottom left hand **CLEAR RELAY** terminal no. **A1**



14. Position and tighten other **RED** cable end into **terminal 4**




15. Locate twin **BLACK** wire. Position **boot-lace** into **terminal 5** and tighten




16. Push the spade connector onto bottom right hand **CLEAR RELAY** terminal no. **A2**

For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.




13. Position and tighten other cable end into the **BLACK RELAY** terminal **A2 TOGETHER WITH** the long **GREY** cable.



14. Position and tighten other **GREY** cable end into **terminal 02**




15. Using the **THIN RED** cable, push the spade connector onto bottom left hand **CLEAR RELAY** terminal no. **A1**




16. Position and tighten other **RED** cable end into **terminal 01**


For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.




17. Position and tighten other cable end into **BLACK RELAY terminal A2**



18. Feed the **LONG RED** cable through the sleeving—bootlace first




19. Position and tighten cable end into terminal block **terminal L**




20. Push the spade connector onto top left hand **CLEAR RELAY terminal no. 21**


For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.



17. Using the **THICK RED** cable, push the spade connector onto bottom left hand **CLEAR RELAY terminal no. 22**



18. Position and tighten other **THICK RED** cable end into **terminal H1**




19. Locate twin **RED & BLACK** wire. Position **bootlace** into **terminal L1** and tighten




20. Push the spade connector onto top left hand **CLEAR RELAY terminal no. 21**

For the details relating to the wiring tray configuration, follow the details shown on the **LEFT HAND** side.



21. Locate twin **RED** wire. Position **bootlace** into **terminal 2** and tighten




22. Push the spade connector onto top right hand **CLEAR RELAY** terminal no. **22**




23. Position and tighten other **RED** cable end into **BLACK RELAY** terminal **14**
24. Carefully replace orange relay if removed
25. Check all cables for tightness.
26. Replace cover
27. Re-install ceiling tile (if removed)
28. Re-instate power and check for operation


For the details relating to the contractors terminal box configuration, follow the details shown on the **RIGHT HAND** side.



21. Position and tighten other **BROWN** cable from **BLACK RELAY** n.o. terminal **11**



22. Locate single **BROWN** wire. Position **bootlace** into **terminal F** and tighten



23. Position and tighten other **BROWN** cable end into **BLACK RELAY** terminal **14**
24. Carefully replace orange relay if removed
25. Check all cables for tightness.
26. Replace cover
27. Re-install ceiling tile (if removed)
28. Re-instate power and check for operation



Ambi-Rad Limited Fens Pool Avenue  
Brierley Hill West Midlands  
DY5 10A United Kingdom  
Telephone 01384 489700  
Facsimile 01384 489707  
UK sales email [sales@ambirad.co.uk](mailto:sales@ambirad.co.uk)  
Website [www.ambirad.co.uk](http://www.ambirad.co.uk)  
Database <http://support.ambirad.co.uk>



**AIRBLOC** is the registered  
Trademark of Ambi-Rad Limited.

Due to continuous product  
innovation, Ambi-Rad reserves  
the right to change product specifi-  
cation without due notice.



An Ambi-Rad Group company